

SDS No. 037-O060306 First issue: 2015/07/23 Revised: 2018/08/29

Safety Data Sheets

1. Identification

Product Name : IJ Primer PR-200

Order No. : PR200-Z-22 / PR200-Z-60 / PR200-Z-BA / PR200-Z-B2

Ink Ver : 2

General Use : Primer for ink jet printer
Product Description : The undercoating liquid

SDS Number : 037-0060306

Manufacture

Company Name : Mimaki Engineering Co., Ltd.

Address : 2182-3 Shigeno-otsu, Tomi-shi, Nagano 389-0512 JAPAN

Telephone No. : +81-268-64-2413

Importer / Distributor Established in USA

Company Name : MIMAKI USA, INC.

Address : 150 Satellite Boulevard, suite A, Suwanee, Georgia 30024, U.S.A.

Telephone No. : +1-678-730-0170 Emergency Telephone No. : +81-268-64-2281

2. Hazards Identification

[HCS Classification]

Physical Hazards

Flammable Liquids : Not classified
Substances and Mixtures, which in : Not classified

Contact with Water, Emit Flammable

Gases

Health Hazards

 $\begin{array}{lll} {\rm Skin\ Corrosion\ /\ Irritation} & : {\rm Category\ 2} \\ {\rm Eye\ Damage\ /\ Irritation} & : {\rm Category\ 2} \\ {\rm Sensitization\ -\ Skin} & : {\rm Category\ 1} \\ \end{array}$

Environmental Hazards

Hazardous to the Aquatic : Category 2

Environment - Acute Hazard

Hazardous to the Aquatic : Category 2

Environment - Long Term Hazard

The above list does not include category being non-classifiable or not-applicable.



Product Name: IJ Primer PR-200 SDS No. 037-0060306 First issue: 2015/07/23

Revised: 2018/08/29

Safety Data Sheets

[GHS Label Elements]

Symbol





Signal Word Warning

Hazard Statements

H315 Causes skin irritation

H317 May cause an allergic skin reaction

H319 Causes serious eye irritation

H411 Toxic to aquatic life with long lasting effects

Precautionary Statements

[Prevention]

P261 Avoid breathing gas/mist/vapours.

P264 Wash hands and eyes thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

[Response]

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/ attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

[Disposal]

P501 Dispose of contents and container in accordance with local, regional, national and international regulation (to be specified).

Statement(s) of Unknown Aquatic Toxicity

45% of the mixture consists of ingredient(s) of unknown acute aquatic toxicity.

40% of the mixture consists of ingredient(s) of unknown chronic aquatic toxicity.

HMIS Rating (scale 0-4)

NFPA Rating (scale 0-4)

Health = 1


Flammability= 0

Reactivity = 0

Protective Equipment =

HealthFlammabilityReactivityProtective Equipment

Health = 1 Flammability = 0 Instability = 0 Special =





SDS No. 037-O060306 First issue: 2015/07/23 Revised: 2018/08/29

3. Composition / Information on Ingredients

No	Chemical Name	Wt%	CAS No.
1	Aliphatic monomer	40-50	Trade Secret
2	Acrylic oligomer	25-35	Trade Secret
3	Aromatic monomer	15-25	Trade Secret
4	Photo-initiator	<10	Trade Secret
5	Additives	<10	Trade Secret

^{*}Acrylic oligomer contains acrylic acid and toluene. And aromatic monomer contains phenyl glycidyl ether

4. First Aid Measures

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable

for breathing. Get medical advice/ attention if you feel unwell.

Get medical advice/ attention if experiencing respiratory symptom. Cover body with blanket to warm and keep at rest. Perform CPR if

not breathing.

Eye Contact : Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. Rinse with clean water for at least 15 minutes and then seek medical attention if necessary. When rinsing, open your eyelids with fingers to insure saturation of water. Seek medical attention if the problem persists.

Skin Contact : Remove/ Take off all contaminated clothing immediately. Wash with

plenty of soap and water. Get immediate medical advice/ attention, if

skin irritation or rash occurs.

Ingestion : Rinse mouth. Do not give an unconscious person anything to drink.

Get immediate medical advice/ attention. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Do not induce

vomiting.

Protection To First-Aiders : Wear appropriate protective equipment if necessary.



SDS No. 037-O060306 First issue: 2015/07/23 Revised: 2018/08/29

5. Fire Fighting Measures

Flammable Properties : Flash point : Approx 106 $^{\circ}$ C

Ignition point : Not available
Flammable point : Not available

Extinguishing Media : Suitable extinguishing media

Fire-extinguishing powder, fire-fighting foam, carbon dioxide, sand,

water spray

Unsuitable extinguishing media

High pressure water jet.

Specific hazards arising

from product

: When exposed to high temperatures, this product may generate

dangerous decompositions such as nitrogen oxides carbon monoxide,

carbon dioxide, and sulfur dioxide.

Specific extinguish

measures

: Cut off the combustion source to the origin of fire and extinguish by

using the appropriate fire extinguishing media. Firefighting measures should be done from windward as much as possible.

Take appropriate measures to disallow substances that may affect the environment from being dispersed by the drainage. Remove all

containers possible to a safe place promptly. If not possible to remove, cool down the area. Work from windward and avoid

inhaling any harmful gases. Use respiratory equipment if necessary.

Special protective

equipment and

precautions

: Cut off the combustion source to the origin of fire and extinguish by

using extinguishing media. Combustion / Flue gases generate carbon monoxide and etc. To avoid the fire from spreading, cool

surrounding area with water spray. Extinguish from windward and

avoid inhaling any harmful gases. Use respiratory equipment if

 $\ensuremath{\mathsf{necessary}}.$ Extinguish from the windward where the gases do not

accumulate and prevent the leakage from spreading. Wear

appropriate protective wear (heat-proof) including air respirators.

Wear respiratory equipment for harmful gases are produced from

combustion or high temperature.



Product Name: IJ Primer PR-200 SDS No. 037-0060306 First issue: 2015/07/23

Revised: 2018/08/29

6. Accidental Release Measures

Personal Precautions

Avoid breathing gas / mist/vapours. Wear protective equipment (boots, gloves, and glasses) to prevent contact with skin. Remove ignition sources in the area and work from windward. Clean up immediately when it spills on the floor or any surface. (The floor surface becomes slippery). Prohibit entry other than related personnel. Ventilate released area. Do not touch and/or walk in the spills. The worker wears an appropriate protective equipment, and avoids eyes, the skin contacts, and inhalations. (refer to Section 8) Provide adequate ventilation if indoors. Cordon off the area and prevent entry of non-related personnel. Work from windward and remove personnel downwind of the area. Wear appropriate protective equipment to prevent contact with skin and inhaling fumes. Remove ignition sources in the area promptly. Prepare fire extinguishing equipment in case of ignition.

Environmental precautions

Avoid releasing to the environment. Collect spillage. Do not empty into drain. If it is mixed with wastewater, drain it after the activated sludge process. Be careful not to influence living organisms and water quality in the environment by products released into rivers and any type of body of water. Contact local authorities if it is flowing into rivers or any type of body of water as necessary. Be careful not to influence the environment by products released into rivers or any type of body of water. If the pollution of water pipes or waterways occur, contact relevant organizations. Clean the area and avoid entry into plumbing system. Be careful not to drain or release untreated waste water into the environment.

Methods and materials for recovery and neutralization

: Contain the flow path with blankets or sand bags and collect into an appropriate container for large spills. Gather and collect into a container for small spills. Prevent the inflow into drains, sewer, basement, or enclosed areas. Clean spills frequently as there is danger of slipping on remnants. Remove all ignition sources.

Smoking, open flame or ignition sources are not allowed in the area. Contain with consideration to safety. Collect into open container by absorbing with cloths, rags, sand or etc. and then rinse with plenty



Product Name: IJ Primer PR-200 SDS No. 037-O060306

> First issue: 2015/07/23 Revised: 2018/08/29

of water. Collect what has scattered into a container that can be sealed. Clean the spilled area with a cloth or a rag. Wear appropriate protective equipment throughout the process.

7. Handling and Storage

Relevant regulation shall be subject to where this product will be handled and stored.

Handling

: Work in accordance with the Occupational Safety and Health Act and related laws and regulations. Keep the concentration below the allowed limit. Avoid inhalation and contact. Wear protection if risk of exposure occurs. Use only in a well-ventilated area. Avoid smoking, open flames, heat and sources of ignition. Always cleanse with soap and water after handling. Determine proper procedures for compliance. Seal container after use. Avoid leakage, overflow, dispersal and generating steam without any good reason. Avoid improper handling like tipping over, dropping, strong impact to or dragging the container. Wash hands thoroughly and rinse mouth after handling. Do not eat, drink or smoke when using this product. Do not carry contaminated gloves and protective equipment into rest / break areas. Prohibit entry to work areas other than related personnel. Collect used containers in a defined / fixed area. Use containers that are not damaged, corroded or cracked. Use local exhaust ventilation systems indoors work areas. Wear proper protective equipment to avoid inhalation and contact with eyes and skin.

Storage

: Store in a well-ventilated area. Protect from sunlight (Ultra Violet-light). Keep container tightly closed. Keep cool. Store in a dark light-safe area. Do not freeze.



Safety Data Sheets

Product Name: IJ Primer PR-200

SDS No. 037-0060306 First issue: 2015/07/23 Revised: 2018/08/29

8. Exposure Controls / Personal Protection

Exposure Limit Values : Not specified

No	Chemical Name		TWA	
1	Acrylic compound	ACGIH	2ppm	
2	Aromatic compound	OSHA	10ppm	
		ACGIH	0.1ppm	
3	Additives	ACGIH	2mg/m³(IFV)	

TWA: Time Weighted Average, IFV: As inhalable fraction and vapor.

Exposure Controls

Occupational Exposure Controls

Engineering Controls : In the case of indoor use, contain at the source or install a local

exhaust system. Provide safety shower and eye / hand wash stations and identify the area clearly. Contain at the source and install a local

exhaust system if dust is generated.

Personal Protection : Wear following protective equipment as necessary and accordingly.

Inspect equipment on a regular basis by using a protective equipment

maintenance chart.

Respiratory : Supplied air respirator, air/oxygen breathing apparatus, organic

Protection vapor gas mask

Vapor Respirator

Hand Protection

otection

Gloves

: Wearing gloves that organic solvents or chemicals do not penetrate is

preferred.

Eye Protection

: Wear coverall, chemical goggles and face shield when handling.





Safety Data Sheets

Product Name: IJ Primer PR-200 SDS No. 037-O060306

> First issue: 2015/07/23 Revised: 2018/08/29

Skin Protection : Wearing protective clothing (long sleeve uniform) that organic

solvent or the chemical do not infiltrate easily preferred.

Environmental Exposure Controls

: Not available

9. Physical and Chemical Properties

Appearance - Physical State : liquid

- Color : Yellow

Odor : Faint

pH : Not Applicable

Boiling Point / Boiling Range $: Approx 181^{\circ}C$

Melting Point / Melting Range : Not available

Flash Point : Approx 106°C

Relative Density : Approx 1.1mg/cm³

Solubility : Not available

Water Solubility : Not available

Partition Coefficient (n-octanol / Water) : Not available

Viscosity : Not available

10. Stability and Reactivity

Reactivity : Decomposes upon heating and produces carbon dioxide and carbon

monoxide.

Conditions to Avoid : Sunlight, heat, open flame, high temperature, sparks, static

electricity, other sources of ignition.

Stability : Stable under normal conditions.

Materials to Avoid : Incompatible with acid, alkali, amines and is prohibited to mix with.

Hazardous Reactions / : Carbon monoxide (CO), carbon dioxide (CO2) gas might be generated

Decomposition Products by combustion. Vapor from organic solvents.



SDS No. 037-0060306 First issue: 2015/07/23

Revised: 2018/08/29

11. Toxicological Information

Acute Toxicity : ORAL

Product LD50(rat): >2000 mg/kg

: DERMAL

Product LD50(rat): >2000 mg/kg

Eye Irritation : Causes severe eye irritation. Category 2 as a product.

Aliphatic compound Category 2

Aromatic compound Category 2

Skin Irritation : Causes moderate skin irritation. Category 2 as a product.

Aliphatic compound Category 2

Aromatic compound Category 2

Skin Sensitization : May cause an allergic skin reaction. Category 1 as a product.

Aromatic compound Category 1

Mutagenicity : No information available.

Carcinogenicity : No information available.

Reproductive and Developmental Toxicity

: No information available.

Specific Target Organ Toxicity (Single Exposure)

: No information available.

Specific Target Organ Toxicity (Repeated Exposure)

: No information available.

Aspiration hazard : No information available.

12. Ecological Information

Handling is noted because it might influence the environment when

leaking and abandoning it.

Especially, note that the product doesn't flow directly to ground, the

river, and the drain ditch.

Ecotoxicity : Toxic to aquatic life.

Aliphatic compound Category 2

Persistence and : No information available.

degradability



Safety Data Sheets

Product Name: IJ Primer PR-200

SDS No. 037-O060306 First issue: 2015/07/23 Revised: 2018/08/29

Bioaccumulative : No information available.

Potential

Mobility in soil : No information available.

Other adverse effects : No information available.

13. Disposal Considerations

Comply with all USA, national and local regulations. A contaminated container and packing are disposed of after removing extraneous matter thoroughly. Follow all regulations in your country or regions.

Do not dump this product into sewers, on the ground or into any body of water.

14. Transport Information

Use a container provided for in the UN Recommendations on the TDG Model Regulations. Avoid direct sunlight during transportation. Confirm the container has no damage, corrosion, leakage before transportation. Take measures to prevent the load from tipping, falling and damages. Follow all regulations on the transport in your countries regions. Verify the container as no leaks when transporting and take preventative measure when loading so that the cargo does not tip, fall or get damaged during transit.

UN Number : 3082

Proper Shipping Name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID N.O.S

Transport hazard : 9 (Miscellaneous dangerous substances & articles)

class(es)

Packing Group(PG) : III

Marine Pollutant : Yes (Product)

Remarks : Single or inner packaging less than 5 L (liquid) or 5 kg net (solids) is

excepted from Dangerous Goods regulations.

Refer to ICAO/IATA A197, IMDG 2.10.2.7, ADR SP 375.



SDS No. 037-0060306 First issue: 2015/07/23 Revised: 2018/08/29

15. Regulatory Information

U.S Federal Regulation : None of this products components are listed under SARA Sections

302/304, SARA Section 313, CERCLA.

SARA Section 311/312 reporting categories: Skin Irritation; Skin

Sensitization; Eye Irritation

TSCA INVENTORY

Chemical name	TSCA INVENTORY	
Aliphatic monomer	Listed	
Acrylic oligomer	No Listed	
Aromatic monomer	Listed	
Photo-initiator	Listed	
Additives	Listed	

SARA Section 311/312 : Acute Health: Yes (40 CFR 370 Subparts B Chronic Health: Yes

and C) 2016 reporting Fire: No

categories Pressure: No

Reactivity: No

California Proposition 65

: WARNING



This product can expose you to chemicals including Phenyl glycidyl ether and Toluene, which are known to the State of California to cause cancer/ birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

: California Proposition 65:

Chemical name	CAS-No.	m wt%	MADL
Phenyl glycidyl ether	122-60-1	< 0.1	5.0 μg/day
Toluene	108-88-3	< 0.1	7000 μg/day

Others Please refer to any other federal, state and local regulations.

16. Other Information

This information is furnished without warranty, express or implied, except that it is accurate to the best knowledge of Mimaki Engineering Corporation.

It relates only to the specific material designated herein, and does not relate to use in combination with any other material or process.



Product Name: IJ Primer PR-200 SDS No. 037-0060306

First issue: 2015/07/23 Revised: 2018/08/29

Safety Data Sheets

Mimaki Engineering Corporation assumes no legal responsibility for use or reliance upon this information.