

# Safety Data Sheets

## 1. Identification

Product Name : SS2 ink White  
Order No. : SPC-0411W-A  
General Use : Ink for ink jet printer  
Product Description : Solvent pigment ink  
SDS Number : 037-S030524  
Manufacture  
Company Name : Mimaki Engineering Co., Ltd.  
Address : 2182-3 Shigeno-otsu, Tomi-shi, Nagano 389-0512 JAPAN  
Telephone No. : +81-268-64-2413  
Importer / Distributor Established in USA  
Company Name : MIMAKI USA, INC.  
Address : 4851 Thurmon Tanner Parkway, STE 100 Flowery Branch, GA  
30542, U.S.A.  
Telephone No. : +1-678-730-0170  
Emergency Telephone No. : +1 866 928 0789 (within United States only, Toll free)  
+1 215 207 0061

## 2. Hazards Identification

### [GHS Classification]

#### Physical Hazards

Flammable Liquids : Category 4

#### Health Hazards

Eye Damage / Irritation : Category 2

Carcinogenicity : Category 2

Specific Target Organ Toxicity : Category 2 (central nervous system)  
(Single Exposure)

#### Environmental Hazards

Hazardous to the Aquatic : Category 3

Environment - Acute Hazard

The above list does not include category being non-classifiable or not-applicable.

## Safety Data Sheets

### [GHS Label Elements]

#### Symbol



#### Signal Word

Danger

#### Hazard Statements

H227 Combustible liquid

H319 Cause serious eye irritation

H351 Suspected of causing cancer

H371 May cause damage to central nervous system

H402 Harmful to aquatic life

#### Precautionary Statements

##### [Prevention]

P201 Obtain SDS (Safety Data Sheet) and printer's operation manual before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. -No smoking.

P260 Do not breathe vapor or mist.

P264 Wash hands thoroughly after handling.

P270 Do not eat, drink, or smoke when using this product.

P273 Avoid release to the environment.

P280 Wear protective gloves/clothing and eye/face protection.

##### [Response]

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P311 IF exposed or concerned: Call a POISON CENTER or doctor/physician.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use appropriate media for extinction.

##### [Storage]

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

##### [Disposal]

P501 Dispose of contents and container in accordance with local, regional, national and international regulation.


#### NFPA Rating (scale 0 – 4)

Health = 2

Flammability = 2

Instability = 0

Special = None



# Safety Data Sheets

## CANADIAN WHMIS SYMBOLS



### 3. Composition / Information on Ingredients

No	Chemical Name	Wt%	CAS No.
1	Glycol ether solvents	70-80	Trade Secret
2	Lactone solvent series	10-20	Trade Secret
3	Titanium dioxide	1-8	13463-67-7
4	Vinyl resin	1-5	Trade Secret

### 4. First Aid Measures

- Inhalation : Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician.
- Eye Contact : Flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical attention.
- Skin Contact : Wash with plenty of soap and water. Take off contaminated clothing and wash before re-use. Get medical attention if irritation develops.
- Ingestion : If swallowed, get medical attention.
- Most Important Symptoms/Effects
- Acute : eye irritation, central nervous system damage
- Delayed : cancer
- Indication of Immediate : Treat symptomatically and supportively.
- Medical Attention and Special Treatment Needed, If Needed

## Safety Data Sheets

### 5. Fire Fighting Measures

Flammable Properties	: Flash point 70.5°C (TCC) Auto Ignition Temperature: 169°C Flammable point : 2.2% to 33.0%
Extinguishing Media	: carbon dioxide, regular dry chemical, water spray, alcohol resistant foam
Unsuitable Extinguishing Media	: Do not scatter spilled material with high-pressure water streams.
Special Hazards Arising from the Chemical	: Combustible liquid and vapor.
Hazardous Combustion Products	: oxides of carbon, oxides of titanium, acid halides
Fire Fighting Measures	: Move container from fire area if it can be done without risk. Do not scatter spilled material with high-pressure water streams. Cool containers with water spray until well after the fire is out. Stay away from the ends of tanks. Avoid inhalation of material or combustion by-products. For fires in cargo or storage area: Cool containers with water from unmanned hose holder or monitor nozzles until well after fire is out. If this is impossible then take the following precautions: Keep unnecessary people away, isolate hazard area and deny entry. Let the fire burn. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire.
Special Protective Equipment and Precautions for Firefighters	: Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

### 6. Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures	: Wear personal protective clothing and equipment, see Section 8. Avoid release to the environment.
---	--

## Safety Data Sheets

Methods and Materials for Containment and Cleaning Up : Eliminate all ignition sources if safe to do so. Stop leak if possible without personal risk. Reduce vapors with water spray.  
**Small spills:** Absorb with sand or other non-combustible material. Collect spilled material in appropriate container for disposal.  
**Large spills:** Dike for later disposal. Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low areas.

### 7. Handling and Storage

Precautions for Safe Handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flame, and hot surfaces - No smoking. Do not breathe vapor or mist. Avoid contact with eyes, skin and clothing. Do not eat, drink, or smoke when using this product. Wear protective gloves and eye/face protection. Wash thoroughly after handling. Avoid release to the environment.

Conditions for Safe Storage, including any Incompatibilities : Store and handle in accordance with all current regulations and standards. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Grounding and bonding required. Store locked up. Keep separated from incompatible substances.

### 8. Exposure Controls / Personal Protection

#### Exposure Limit Values

No	Chemical Name		TWA
1	Titanium dioxide (13463-67-7)	ACGIH:	10 mg/m <sup>3</sup> TWA
		OSHA:	15 mg/m <sup>3</sup> TWA (total dust)
		Mexico	10 mg/m <sup>3</sup> TWA LMPE-PPT (as Ti) 20 mg/m <sup>3</sup> STEL [LMPE-CT] (as Ti)

Component Biological Limit Values : There are no biological limit values for the component(s) of this product.

# Safety Data Sheets

## Exposure Controls

### Occupational Exposure Controls

Appropriate : Ventilation equipment should be explosion-resistant if explosive concentrations of material are present. Provide local exhaust or Engineering Controls process enclosure ventilation system. Ensure compliance with applicable exposure limits.

## Personal Protection

Respiratory : Consult with a health and safety professional for specific respirators Protection appropriate for your use.



Hand Protection : Wear appropriate chemical resistant gloves.



Eye Protection : Wear splash resistant safety goggles with a faceshield. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.



**Safet**

Skin Protection : Wear appropriate chemical resistant clothing.



## 9. Physical and Chemical Properties

Appearance	- Physical State	: Liquid
	- Color	: White
Odor		: slight solvent odor
pH		: Not available
Boiling Point / Boiling Range		: >=176 °C
Melting Point / Melting Range		: Not available
Decomposition Temperature		: Not available
Flash Point		: 70.5°C (closed cup)

## Safety Data Sheets

Auto ignition temperature	: 169°C
Flammability (Solid, Gas)	: Not applicable
Explosive Properties	: Not available
Oxidizing Properties	: Not available
Upper / Lower Flammability or Explosive Limits	: 2.2% to 33.0%
Vapor Pressure	: Less than 133Pa(20°C)
Specific Gravity	: 1.01±0.01 (20 °C)
Solubility	: Not available
Water Solubility	: Not available
Partition Coefficient (n-octanol / Water)	: Not available
Viscosity	: 4.8±0.3(20° C)
Vapor Density	: Not available
Evaporation Rate	: Not available
VOC	: 923.1 g/L

### 10. Stability and Reactivity

Reactivity	: No reactivity hazard is expected.
Chemical Stability	: Stable under normal conditions of use.
Possibility of Hazardous Reactions	: Will not polymerize.
Conditions to Avoid	: Avoid flames, sparks, and other sources of ignition. Containers may rupture or explode if exposed to heat. Avoid contact with incompatible materials.
Incompatible Materials	: acids, bases, oxidizing materials, metals, halogens
Hazardous Decomposition	: Combustion: oxides of carbon, oxides of titanium, acid halides

### 11. Toxicological Information

Acute Toxicity	: The component(s) of this material have been reviewed in various sources and the following selected endpoints are published:
----------------	---

Component Analysis -  
LD50/LC50

**Glycol ether solvents (Proprietary)**

Oral LD50 Rat 6500 µL/kg

# Safety Data Sheets

**Lactone solvent series (Proprietary)**

Oral LD50 Rat 1540 mg/kg; Inhalation LC50 Rat >5100 mg/m<sup>3</sup> 4 h

**Titanium dioxide (13463-67-7)**

Oral LD50 Rat >10000 mg/kg

Information on Likely Routes of Exposure

- Inhalation : irritation, nausea, headache, drowsiness, dizziness, loss of coordination, unconsciousness, coma, cough, cancer
- Ingestion : irritation, nausea, headache, drowsiness, dizziness, loss of coordination, unconsciousness, coma
- Skin Contact : irritation, nausea, headache, drowsiness, dizziness, unconsciousness, coma
- Eye Contact : irritation, eye damage
- Immediate Effects : eye irritation, central nervous system damage
- Delayed Effects : cancer
- Medical Conditions : respiratory disorders
- Aggravated by Exposure
- Irritation/Corrosivity : eye irritation
- Data
- Respiratory : No information available for the product.
- Sensitization
- Dermal Sensitization : No information available for the product.
- Germ Cell Mutagenicity : No information available for the product.
- Carcinogenicity : Component Carcinogenicity

**Lactone solvent series (Proprietary)**

IARC:	Monograph 71 [1999]; Supplement 7 [1987]; Monograph 11 [1976] (Group 3 (not classifiable))
-------	---

**Titanium dioxide (13463-67-7)**

ACGIH:	A4 - Not Classifiable as a Human Carcinogen
IARC:	Monograph 93 [2010]; Monograph 47 [1989] (Group 2B (possibly carcinogenic to humans))
DFG:	Category 3A (could be carcinogenic for man, inhalable fraction with the exception of ultra small particles)
OSHA:	Present

**Vinyl resin (Proprietary)**

IARC:	Supplement 7 [1987]; Monograph 19 [1979] (Group 3)
-------	--

## Safety Data Sheets

	(not classifiable)
--	--------------------

Reproductive Toxicity : No information available for the product.  
 Specific Target Organ : central nervous system  
 Toxicity - Single Exposure  
 Specific Target Organ : No target organs identified.  
 Toxicity - Repeated Exposure  
 Aspiration Hazard : No information available for the product.

### 12. Ecological Information

Handling is noted because it might influence the environment when leaking and abandoning it.  
 Especially, note that the product doesn't flow directly to ground, the river, and the drain ditch.

Ecotoxicity : Harmful to aquatic life.  
 Component Analysis - : Lactone solvent series (Proprietary)

Aquatic Toxicity	Algae:	72 Hr EC50 <i>Desmodesmus subspicatus</i> : 360 mg/L; 96 Hr EC50 <i>Desmodesmus subspicatus</i> : 79 mg/L
	Invertebrate:	48 Hr EC50 <i>Daphnia magna</i> Straus: >500 mg/L

Persistence and Degradability : Not available  
 Bioaccumulation : Not available  
 Mobility : Not available  
 Other Toxicity : Not available

### 13. Disposal Considerations

: Comply with all USA, national and local regulations.  
Do not dump this product into sewers, on the ground or into any body of water.

Disposal Methods : Dispose in accordance with all applicable regulations.  
 Component Waste Numbers : The U.S. EPA has not published waste numbers for this product's components.

## Safety Data Sheets

Disposal of Contaminated Packaging : Empty containers may contain product residue. Dispose in accordance with all applicable regulations.

### 14. Transport Information

Check a thing without a leak in a container.

Perform prevention of collapse of cargo surely.

#### US DOT Information

Shipping Name : Combustible liquid, n.o.s.  
(Contains: Glycol ether solvents, Lactone solvent series)  
UN Number : NA1993  
Hazardous Class : Combustible liquid

Packing Group (PG) : III

TDG Information : Not regulated as dangerous goods for transport.

Marine Pollutant : Lactone solvent series (Proprietary)

IBC Code: Category Y

Titanium dioxide (13463-67-7)

IBC Code: Category Z (slurry)

### 15. Regulatory Information

U.S. Federal Regulations : None of this products components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 311/312 (40 CFR 370.21), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

SARA Title III Section 311/312 : Acute Health: Yes  
Chronic Health: Yes  
Fire: Yes  
Pressure: No  
Reactive: No

# Safety Data Sheets

U.S. State Regulations : The following components appear on one or more of the following state hazardous substances lists:

Component	CAS No.	CA	MA	MN	NJ	PA
Titanium dioxide	13463-67-7	No	Yes	Yes	Yes	Yes

California Proposition : **WARNING:**

65



This product can expose you to chemicals including Cadmium and cadmium compounds, Lead and lead compounds, Mercury and mercury compounds, Nickel compounds, Titanium dioxide, Vinyl Chloride, which is known to the State of California to cause cancer/ birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Canada : WHMIS CLASSIFICATION: B3, D2A, D2B.

Canadian WHMIS : None of the product component(s) are listed on the Ingredients Disclosure List (IDL).

List (IDL)

Chemical Inventory : Component Analysis - Inventory

Listings

Component	US	CA	EU	AU	PHIL	JP	KR	CN	NZ
Glycol ether solvents (Proprietary)	Yes	NSL	EIN	No	No	Yes	No	Yes	No
Lactone solvent series (Proprietary)	Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	Yes
Titanium dioxide (13463-67-7)	Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	Yes
Vinyl resin (Proprietary)	Yes	DSL	No	Yes	Yes	Yes	Yes	Yes	Yes

## 16. Other Information

Key/Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; CAS - Chemical Abstracts Service; CLP - Classification, Labelling and Packaging; EEC - European Economic Community; EIN (EINECS) - European Inventory of Existing Commercial Chemical Substances; ELN (ELINCS) - European List of Notified Chemical

## Safety Data Sheets

Substances; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IMDG - International Maritime Dangerous Goods; IBC Code - International Bulk Chemical Code; Kow - Octanol/water partition coefficient; LEL - Lower Explosive Limit; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NTP = National Toxicology Program; REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - European Rail Transport; STEL - Short-term Exposure Limit; TWA - Time Weighted Average; UEL - Upper Explosive Limit

### Other Information

This information is furnished without warranty, express or implied, except that it is accurate to the best knowledge of Mimaki Engineering Corporation.

It relates only to the specific material designated herein, and does not relate to use in combination with any other material or process.

Mimaki Engineering Corporation assumes no legal responsibility for use or reliance upon this information.