

SDS No. 037-S080500 First issue: 2007/07/31

Revised: 2018/09/06

Safety Data Sheets

1. Identification

Product Name : SS21 ink Light Magenta

Order No. : SPC-0501LM / SPC-0588LM

General Use : Ink for ink jet printer Product Description : Solvent pigment ink

SDS Number : 037-S080500

Manufacture

Company Name : Mimaki Engineering Co., Ltd.

Address : 2182-3 Shigeno-otsu, Tomi-shi, Nagano 389-0512 JAPAN

Telephone No. : +81-268-64-2413

Importer / Distributor Established in USA

Company Name : MIMAKI USA, INC.

Address : 150 Satellite Boulevard, suite A, Suwanee, Georgia 30024, U.S.A.

Telephone No. : +1-678-730-0170 Emergency Telephone No. : +81-268-64-2281

2. Hazards Identification

[GHS Classification]

Physical Hazards

Flammable Liquids : Category 4

Health Hazards

Acute Toxicity - Oral : Category 4 (70-85% unknown)

Eye Damage / Irritation : Category 2

Specific Target Organ Toxicity : Category 2 (central nervous system)

(Single Exposure)

Specific Target Organ Toxicity : Category 3 (drowsiness and dizziness)

(Repeated Exposure)

Environmental Hazards

Hazardous to the Aquatic : Category 3

Environment - Acute Hazard

The above list does not include category being non-classifiable or not-applicable.



SDS No. 037-S080500 First issue: 2007/07/31 Revised: 2018/09/06

Safety Data Sheets

[GHS Label Elements] Symbol





Signal Word Warning

Hazard Statements

H227 Combustible liquid

H302 Harmful if swallowed

H319 Cause serious eye irritation

H371 May cause damage to central nervous system

H336 May cause drowsiness and dizziness

H402 Harmful to aquatic life

Precautionary Statements

[Prevention]

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P260 Do not breathe vapor or mist.

P264 Wash hands thoroughly after handling.

P270 Do not eat, drink, or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/clothing and eye/face protection.

[Response]

P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P311 IF exposed or concerned: Call a POISON CENTER or doctor/physician.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P330 Rinse mouth.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use appropriate media for extinction.

Storage

P403+P233+P235 Store in a well-ventilated place. Keep container tightly closed. Keep cool.

P405 Store locked up.

[Disposal]

P501 Dispose of contents and container in accordance with local, regional, national and international regulation.



SDS No. 037-S080500 First issue: 2007/07/31

Revised: 2018/09/06

NFPA Rating (scale 0-4)

Health = 2

Flammability = 2

Instability = 0

Special = None



CANADIAN WHMIS SYMBOLS: B3, D2B





Composition / Information on Ingredients

No	Chemical Name	Wt%	CAS No.
1	Glycol ether solvents	65-75	Trade Secret
2	Lactone solvent series	15-25	Trade Secret
3	Vinyl resin	1-5	Trade Secret
4	Propylene glycol monomethyl ether acetate	1-5	108-65-6
5	Quinacridone pigment series	0.1-5	Trade Secret

First Aid Measures

Inhalation Remove person to fresh air and keep comfortable for breathing. Call

a POISON CENTER or doctor/physician.

Eye Contact : Flush eyes with plenty of water for at least 15 minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. Get

immediate medical attention.

Skin Contact : Wash with plenty of soap and water. Take off contaminated clothing

and wash before re-use. Get medical attention if irritation develops.

: If swallowed, get medical attention. Ingestion

Most Important Symptoms/Effects

Acute : eye irritation, central nervous system depression, central nervous

system damage

Delayed : no information on significant adverse effects



Product Name: SS21 ink Light Magenta SDS No. 037-S080500

First issue: 2007/07/31

Revised: 2018/09/06

Safety Data Sheets

Indication of Immediate

Medical Attention and

Special Treatment

Needed, If Needed

: Treat symptomatically and supportively.

Fire Fighting Measures

Flammable Properties : Flash point 69.2°C (TCC)

Auto Ignition Temperature: 169°C

Extinguishing Media : carbon dioxide, regular dry chemical, water spray, alcohol resistant

foam

Unsuitable Extinguishing

Media

Special Hazards Arising

from the Chemical

Hazardous Combustion

Products

Fire Fighting

Measures

Flammable point : 2.2% to 33.0%

: Do not scatter spilled material with high-pressure water streams.

: Combustible liquid and vapor.

: oxides of carbon, acid halides

: Move container from fire area if it can be done without risk. Do not scatter spilled material with high-pressure water streams. Cool containers with water spray until well after the fire is out. Stay away from the ends of tanks. Avoid inhalation of material or combustion by-products. For fires in cargo or storage area: Cool containers with water from unmanned hose holder or monitor nozzles until well after fire is out. If this is impossible then take the following precautions: Keep unnecessary people away, isolate

hazard area and deny entry. Let the fire burn. Withdraw

immediately in case of rising sound from venting safety device or

any discoloration of tanks due to fire.

Special Protective

Equipment and

Precautions for

Firefighters

: Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible

exposure.



SDS No. 037-S080500 First issue: 2007/07/31

Revised: 2018/09/06

6. Accidental Release Measures

Personal Precautions,

Protective Equipment

and Emergency

Procedures

Methods and Materials

for Containment and

Cleaning Up

: Wear personal protective clothing and equipment, see Section 8.

Avoid release to the environment.

: Eliminate all ignition sources if safe to do so. Stop leak if possible

without personal risk. Reduce vapors with water spray.

Small spills: Absorb with sand or other non-combustible material.

Collect spilled material in appropriate container for disposal.

Large spills: Dike for later disposal. Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low

areas.

7. Handling and Storage

Precautions for Safe

Handling

: Keep away from heat, sparks, open flame, and hot surfaces - No

smoking. Do not breathe vapor or mist. Use only outdoors or in a well-ventilated area. Avoid contact with eyes, skin and clothing. Do

not eat, drink, or smoke when using this product. Wear protective

gloves and eye/face protection. Wash thoroughly after handling. Avoid

release to the environment.

Conditions for Safe

Storage, including any

Incompatibilities

: Store and handle in accordance with all current regulations and $% \left(1\right) =\left(1\right) =\left(1\right)$

standards. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Grounding and bonding required. Store locked up.

Keep separated from incompatible substances.

8. Exposure Controls / Personal Protection

Exposure Limit Values

: ACGIH, OSHA, and NIOSH have not developed exposure limits for

any of this product's components.

Component Biological

Limit Values

: There are no biological limit values for the component(s) of this

product.



Safety Data Sheets

Product Name: SS21 ink Light Magenta

SDS No. 037-S080500 First issue: 2007/07/31

Revised: 2018/09/06

Exposure Controls

Occupational Exposure Controls

: Ventilation equipment should be explosion-resistant if explosive Appropriate

Engineering Controls concentrations of material are present. Provide local exhaust or

process enclosure ventilation system. Ensure compliance with

applicable exposure limits.

Personal Protection

Respiratory : Consult with a health and safety professional for specific respirators

Protection appropriate for your use.

Hand Protection

: Wear appropriate chemical resistant gloves.



Eve Protection



Skin Protection



emergency eye wash fountain and quick drench shower in the immediate work area.

: Wear splash resistant safety goggles with a faceshield. Provide an

: Wear appropriate chemical resistant clothing.



Physical and Chemical Properties

- Physical State : Liquid Appearance

> - Color : Red

Odor : slight solvent odor

pН : Not available

:>=124 °C Boiling Point / Boiling Range

: Not available Melting Point / Melting Range **Decomposition Temperature** : Not available

Flash Point : 69.2℃



Safety Data Sheets

Product Name: SS21 ink Light Magenta

SDS No. 037-S080500 First issue: 2007/07/31

Revised: 2018/09/06

Auto ignition temperature : 169°C

Flammability (Solid, Gas) : Not applicable
Explosive Properties : Not available
Oxidizing Properties : Not available
Upper / Lower Flammability or : 2.2% to 33.0%

Explosive Limits

Vapor Pressure : Less than 133Pa(20°C)

: 0.984 (20 °C) Specific Gravity : Not available Solubility Water Solubility : Not available Partition Coefficient (n-octanol / Water) : Not available $: 4.2 \pm 0.3(20^{\circ} \text{ C})$ Viscosity Vapor Density : Not available **Evaporation Rate** : Not available VOC : 933.8 g/L

10. Stability and Reactivity

Reactivity : No reactivity hazard is expected.

Chemical Stability : Stable under normal conditions of use.

Possibility of Hazardous : Will not polymerize.

Reactions

Conditions to Avoid : Avoid flames, sparks, and other sources of ignition. Containers may

rupture or explode if exposed to heat. Avoid contact with incompatible

materials.

Incompatible Materials : acids, bases, oxidizing materials, halogens

Hazardous : Combustion: oxides of carbon, acid halides

Decomposition

11. Toxicological Information

Acute Toxicity : The component(s) of this material have been reviewed in various

Component Analysis - sources and the following selected endpoints are published:

LD50/LC50 Propylene glycol monomethyl ether acetate (108-65-6)

Dermal LD50 Rabbit >5 g/kg; Oral LD50 Rat 8532 mg/kg



SDS No. 037-S080500 First issue: 2007/07/31

Revised: 2018/09/06

Safety Data Sheets

Lactone solvent series (Proprietary)

Inhalation LC50 Rat >5100 mg/m3 4 h; Oral LD50 Rat 1540 mg/kg

Information on Likely Routes of Exposure

Inhalation : irritation, nausea, headache, drowsiness, dizziness, loss of

coordination, unconsciousness, coma, kidney damage, liver damage

Ingestion : irritation, nausea, headache, drowsiness, dizziness, loss of

coordination, unconsciousness, coma

Skin Contact : irritation, nausea, headache, drowsiness, dizziness, unconsciousness,

coma

Eye Contact : irritation

Immediate Effects : eye irritation, central nervous system depression, drowsiness,

dizziness

Delayed Effects : no information on significant adverse effects

Medical Conditions : No information available for the product.

Aggravated by Exposure

Irritation/Corrosivity : eye irritation

Data

Respiratory : No information available for the product.

Sensitization

Dermal Sensitization : No information available for the product. : No information available for the product. Germ Cell Mutagenicity

: Component Carcinogenicity Carcinogenicity

Lactone solvent series (Proprietary)

IARC:	Monograph 71 [1999]; Supplement 7 [1987];
IAIC.	Monograph 11 [1976] (Group 3 (not classifiable))

Vinyl resin (Proprietary)

IARC:	Supplement 7 [1987]; Monograph 19 [1979] (Group				
IAIVO.	(not classifiable))				

Reproductive Toxicity : No information available for the product.

Specific Target Organ : central nervous system, drowsiness, dizziness

Toxicity - Single

Exposure

Specific Target Organ : No target organs identified.

Toxicity - Repeated

Exposure

Aspiration Hazard : No information available for the product.



Safety Data Sheets

Product Name: SS21 ink Light Magenta

SDS No. 037-S080500 First issue: 2007/07/31

Revised: 2018/09/06

12. Ecological Information

Handling is noted because it might influence the environment when

leaking and abandoning it.

Especially, note that the product doesn't flow directly to ground, the

river, and the drain ditch.

Component Analysis -

: Propylene glycol monomethyl ether acetate (108-65-6)

Aquatic Toxicity

Fish:	96 Hr LC50 Pimephales promelas: 161 mg/L [static]					
Invertebrate:	48 Hr EC50 Daphnia magna Straus: >500 mg/L					

Lactone solvent series (Proprietary)

A.1	72 Hr EC50 Desmodesmus subspicatus: 360 mg/L;					
Algae:	96 Hr EC50 Desmodesmus subspicatus: 79 mg/L					
Invertebrate:	48 Hr EC50 Daphnia magna Straus: >500 mg/L					

Persistence and

: Not available

Degradability

: Not available Bioaccumulation Mobility : Not available : Not available Other Toxicity

13. Disposal Considerations

: Comply with all USA, national and local regulations.

Do not dump this product into sewers, on the ground or into any body

of water.

Disposal Methods : Dispose in accordance with all applicable regulations.

Component Waste : The U.S. EPA has not published waste numbers for this product's

Numbers components.

Disposal of : Empty containers may contain product residue. Dispose in

Contaminated accordance with all applicable regulations.

Packaging



SDS No. 037-S080500 First issue: 2007/07/31

Revised: 2018/09/06

14. Transport Information

Check a thing without a leak in a container.

Perform prevention of collapse of cargo surely.

IATA Information
 Not regulated as dangerous goods for transport.
 ICAO Information
 Not regulated as dangerous goods for transport.
 IMDG Information
 Not regulated as dangerous goods for transport.

Marine Pollutant : Lactone solvent series (Proprietary)

IBC Code: Category Y

Propylene glycol monomethyl ether acetate (108-65-6)

IBC Code: Category Z

 $TDG\ Information \\ \hspace*{0.5in} \vdots \ Not\ regulated\ as\ dangerous\ goods\ for\ transport.$

US DOT Information : Not regulated as dangerous goods for transport. *1

15. Regulatory Information

U.S. Federal : None of this products components are listed under SARA Sections

Regulations 302/304 (40 CFR 355 Appendix A), SARA Section 311/312 (40 CFR

370.21), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4),

TSCA 12(b), or require an OSHA process safety plan.

SARA TitleIII : Acute Health: Yes

Section 311/312 Chronic Health: No

Fire: Yes

Pressure: No Reactive: No

U.S. State Regulations : None of this product's components are listed on the state lists from

MA, MN, NJ or PA.

California Proposition : WARNING:

This product can expose you to chemicals including Vinyl

Chloride, which is known to the State of California to cause

cancer. For more information go to www.P65Warnings.ca.gov.

Canada : WHMIS CLASSIFICATION: B3, D2B.

Canadian WHMIS : None of the product component(s) are listed on the Ingredients

^{*1} Class combustible liquid (NA1993), Packing group III for quantities of 450 liters (119 gallons) or more; not regulated for smaller quantities



SDS No. 037-S080500 First issue: 2007/07/31 Revised: 2018/09/06

Safety Data Sheets

Ingredient Disclosure List (IDL).

List (IDL)

Chemical Inventory : Component Analysis - Inventory

Listings

Component	US	CA	EU	AU	PHIL	JP	KR	CN	NZ
Glycol ether solvents	Yes	NSL	EIN	No	No	Yes	No	Yes	No
(Proprietary)									
Propylene glycol	Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	Yes
monomethyl ether									
acetate(108-65-6)									
Lactone solvent series	Yes DSL	DGI	EIN	V	Yes	Yes	Vac	Yes	V
(Proprietary)		EIN	Yes	res	ies	Yes	ies	Yes	
Vinyl resin	V	DCI	M.	37	V	V	V	V	V
(Proprietary) Yes	DSL	No	Yes	Yes	Yes	Yes	Yes	Yes	

16. Other Information

Key/Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; CAS - Chemical Abstracts Service; CLP - Classification, Labelling and Packaging; EEC - European Economic Community; EIN (EINECS) - European Inventory of Existing Commercial Chemical Substances; ELN (ELINCS) - European List of Notified Chemical Substances; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IMDG - International Maritime Dangerous Goods; IBC Code - International Bulk Chemical Code; Kow - Octanol/water partition coefficient; LEL - Lower Explosive Limit; LOLI - List Of LIstsTM - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NTP = National Toxicology Program; REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - European Rail Transport; STEL - Short-term Exposure Limit; TWA - Time Weighted Average; UEL - Upper Explosive Limit



SDS No. 037-S080500 First issue: 2007/07/31

Revised: 2018/09/06

Other Information

This information is furnished without warranty, express or implied, except that it is accurate to the best knowledge of Mimaki Engineering Corporation.

It relates only to the specific material designated herein, and does not relate to use in combination with any other material or process.

Mimaki Engineering Corporation assumes no legal responsibility for use or reliance upon this information.