

1. Identification

Product Name	: UV ink F-200 Magenta	
Order No.	: SPC-0516M-2	
General Use	: Ink for ink jet printer	
Product Description	: UV Inkjet Ink	
SDS Number	: 037-U040551	
Manufacture		
Company Name	: Mimaki Engineering Co., Ltd.	
Address	2182-3 Shigeno-otsu, Tomi-shi, Nagano 389-0512 JAPAN	
Telephone No.	: +81-268-64-2413	
Importer / Distributor Established in USA		
Company Name	: MIMAKI USA, INC.	
Address	: 150 Satellite Boulevard, suite A, Suwanee, Georgia 30024, U.S.A.	
Telephone No.	: +1-678-730-0170	
Emergency Telephone No.	: +1 866 928 0789 (within United States only, Toll free)	
	$+1\ 215\ 207\ 0061$	

2. Hazards Identification

[GHS Classification]	
Physical Hazards	
Flammable Liquids	: Not classified
Health Hazards	
Acute Toxicity – Oral	: Category 4
Skin Corrosion / Irritation	Category 2
Eye Damage / Irritation	: Category 2A
Sensitization - Skin	: Category 1B
Carcinogenicity	Category 2
Toxic to Reproduction	Category 2
Specific Target Organ Toxicity	: Category 2 (kidney/urinary tract/Skin)
(Repeated Exposure)	

The above list does not include category being non-classifiable or not-applicable.



Product Name: UV ink F-200 Magenta SDS No. 037-U040551 First issue: 2009/02/24 Revised: 2021/11/18

Safety Data Sheets

[GHS Label Elements]



Signal Word Warning

Hazard Statements

H302 Harmful if swallowed H315 Causes skin irritation

H317 May cause an allergic skin reaction

H319 Causes serious eye irritation

H351 Suspected of causing cancer

H361 Suspected of damaging fertility or the unborn child

H373 May cause damage to organs through prolonged or repeated exposure (kidney/urinary tract/Skin)

Precautionary Statements

[Prevention]

P201 Obtain SDS (Safety Data Sheet) and printer's operation manual before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe vapor/mist.

P264 Wash hands and eyes thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

[Response]

P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

(P301+)P330 (IF SWALLOWED:) Rinse mouth.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash before re-use.

[Storage]

P405 Store locked up.

[Disposal]

P501 Dispose of contents/container in accordance with local/regional/national/international regulation (to be specified).


[Hazards not otherwise classified]

16% of the mixture consists of ingredients of unknown acute oral toxicity.

38% of the mixture consists of ingredients of unknown acute dermal toxicity.

Mimciki Safety Data Sheets

NFPA Rating (scale 0 - 4)



3. Composition / Information on Ingredients

No	Chemical Name	Wt%	CAS No.
1	ISOBORNYL ACRYLATE	15 - 25	5888-33-5
2	ISOOCTYL ACRYLATE	15 - 25	29590-42-9
3	TETRAHYDROFURFURYL ACRYLATE	15 - 25	2399-48-6
4	1,6-HEXANEDIOL DIACRYLATE	1 - 10	13048-33-4
5	2,4,6-TRIMETHYLBENZOYLDIPHENYL PHOSPHINE	1 - 10	75980-60-8
6	BENZOPHENONE	1 - 10	119-61-9
7	ALIPHATIC URETHANE ACRYLATE	1 - 10	Trade Secret
8	AMINE MODIFIED ACRYLATE OLIGOMER	1 - 10	Trade Secret
9	ORGANIC PIGMENT	1 - 10	Trade Secret
10	POLYALKYLENE IMINE TS#800967-5312	1 - 5	Trade Secret
11	TETRAHYDROFURFURYL ALCOHOL	< 0.5	97-99-4

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

4. First Aid Measures

Inhalation	Remove person to fresh air. If you feel unwell, get medical attention.
Eye Contact	: Immediately flush with large amounts of water. Remove contact
	lenses if easy to do. Continue rinsing. Get medical attention.
Skin Contact	: Immediately wash with soap and water. Remove contaminated
	clothing and wash before reuse. If signs/symptoms develop,get
	medical attention.
Ingestion	Rinse mouth. If you feel unwell, get medical attention.

Most important	: See Section 11.1. Information on toxicological effects.
symptoms and effects,	
both acute and delayed	
Indication of Immediate	: Not applicable.
Medical Attention and	
Special Treatment	
Needed, If Needed	

5. Fire Fighting Measures

Flammable Properties	: Flash point >200° F
Extinguishing Media	: Use a fire fighting agent suitable for ordinary combustible material
	such as water or foam to extinguish.
Special Hazards Arising	Closed containers exposed to heat from fire may build pressure and
from the Chemical	explode.
Hazardous Combustion	Carbon monoxide, Carbon dioxide (During Combustion)
Products	
Special protective actions	: Water may not effectively extinguish fire; however, it should be used
for fire-fighters	to keep fire-exposed containers and surfaces cool and prevent
	explosive rupture.

6. Accidental Release Measures

Personal precautions,	: Evacuate area. Ventilate the area with fresh air. For large spill, or
protective equipment and	spills in confined spaces, provide mechanical ventilation to disperse
emergency procedures	or exhaust vapors, in accordance with good industrial hygiene
	practice. Warning! A motor could be an ignition source and could
	cause flammable gases or vapors in the spill area to burn or explode.
	Refer to other sections of this SDS for information regarding
	physical and health hazards, respiratory protection, ventilation, and
	personal protective equipment.
Environmental	: Avoid release to the environment. For larger spills, cover drains and
precautions	build dikes to prevent entry into sewer systems or bodies of water.

Methods and material for containment and cleaning up Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible.

7. Handling and Storage

Precautions for Safe	Avoid skin contact with hot material. For industrial or professional
Handling	use only. Do not handle until all safety precautions have been read
	and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do
	not get in eyes, on skin, or on clothing. Do not eat, drink or smoke
	when using this product. Wash thoroughly after handling.
	Contaminated work clothing should not be allowed out of the
	workplace. Avoid release to the environment. Wash contaminated
	clothing before reuse. Avoid contact with oxidizing agents (eg.
	chlorine, chromic acid etc.) Use personal protective equipment
	(gloves, respirators, etc.) as required.
Conditions for Safe	[:] Keep cool. Protect from sunlight. Store away from heat. Store away
Storage, including any	from oxidizing agents.
Incompatibilities	

8. Exposure Controls / Personal Protection

Exposure Limit Values : If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.



Ingredient	CAS No.	Agency	Limit type	Additional
				Comments
BENZOPHENONE	119-61-9	AIHA	TWA:0.5 mg/m ³	
1,6-HEXANEDIOL	13048-33-4	AIHA	TWA:1 mg/m ³	Dermal
DIACRYLATE			(0.11 ppm)	Sensitizer
TETRAHYDROFURFURYL	2399-48-6	Manufacturer	TWA:0.1 ppm	
ACRYLATE		determined	$(0.64 \text{mg/m}^3);$	
			STEL:0.3 ppm	
			(1.91mg/m^3)	
ISOOCTYL ACRYLATE	29590-42-9	AIHA	TWA:37.5 mg/m ³	
			(5 ppm)	
		Manufacturer	TWA:5 ppm	
		determined		
TETRAHYDROFURFURYL	97-99-4	AIHA	TWA:2 mg/m ³ (0.5	
ALCOHOL			ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Exposure Controls

Occupational Exposure Controls

Appropriate: Use general dilution ventilation and/or local exhaust ventilation toEngineering Controlscontrol airborne exposures to below relevant Exposure Limits and/or
control dust/fume/gas/mist/vapors/spray. If ventilation is not
adequate, use respiratory protection equipment.

Personal Protection

Respiratory

Protection



: An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

Gloves

Skin/Hand

Protection

Apron

For questions about suitability for a specific application, consult with your respirator manufacturer.

: Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Eye Protection



: Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Indirect Vented Goggles

9. Physical and Chemical Properties

Appearance	- Physical State	: Liquid	
	- Color	: Magenta	
Odor		: Acrylate Odor,	
pН		: Not Applicable	
Boiling Point / Boiling Range		$:>200^{\circ}$ F	
Melting Point / Melting Range		: Not available	
Decomposition Temperature		: Not available	
Flash Point		200° F [Test Method: Closed Cup]	
Auto ignition temperature		: Not available	
Flammability (Solid, Gas)		: Not Applicable	

MIMCIKI[®] Safety Data Sheets

Product Name: UV ink F-200 Magenta SDS No. 037-U040551 First issue: 2009/02/24 Revised: 2021/11/18

Explosive Properties	: Not available
Oxidizing Properties	: Not available
Upper / Lower Flammability or	: Not available
Explosive Limits	
Vapor Pressure	∶<10 mmHg [@ 20 °C]
Specific Gravity	: 1.04 [Ref Std: WATER=1]
Solubility	: Not available
Water Solubility	: Negligible
Partition Coefficient (n-octanol / Water)	: Not available
Viscosity	: Not available
Vapor Density	: > 1 [Ref Std: AIR=1]
Evaporation Rate	: Not available
VOC	: Not available

10. Stability and Reactivity

Reactivity	: This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.
Chemical Stability	Stable under normal conditions of use.
Possibility of Hazardous	: Hazardous polymerization will not occur.
Reactions	
Conditions to Avoid	: Heat
Incompatible Materials	: Strong oxidizing agents
Hazardous	: None known.
Decomposition	

Refer to section 5.2 for hazardous decomposition products during combustion

11. Toxicological In	formation
Inholation	· Despiretowy Treast Invitation: Signal symptoms may include sough

Inhalation : Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact	swelling, it Skin React redness, sv	Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching. May cause additional			
Eye Contact	: Severe Eye redness, sv	velling, pain, tearing, cl	toms may include significant oudy appearance of the cornea, and		
Ingestion	may includ	swallowed. Gastrointes le abdominal pain, stom	stinal Irritation: Signs/symptoms nach upset, nausea, vomiting and		
Additional Health Effec		May cause additional he	ealth effects (see below).		
Prolonged or repeated		adder Effects: Signs/syn	nptoms may include changes in		
exposure may cause			wer back pain, increased protein in		
target organ effects	urine, incr	eased blood urea nitrog	en (BUN), blood in urine, and		
	painful uri	nation.			
	Dermal Ef	fects: Signs/symptoms r	nay include redness, itching, acne,		
	or bumps o	on the skin.			
Reproductive/Developm	e : Contains a	chemical or chemicals	which can cause birth defects or		
ntal Toxicity	other repro	oductive harm.			
Carcinogenicity	: Contains a	chemical or chemicals	which can cause cancer.		
Ingredient	CAS No.	Class Description	Regulation		
BENZOPHENONE	119-61-9	Grp. 2B: Possible	International Agency for		
		human carc.	Research on Cancer		
Toxicological Data	: If a compo	nent is disclosed in sect	ion 3 but does not appear in a table		
below, either no data are available for that endpoint or the data are					

not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
	Dermal		No data available;
			calculated
Overall product			ATE > 5,000 mg/kg
	Ingestion		No data available;
			calculated



			ATE 300 - 2,000
			mg/kg
TETRAHYDROFURFURYL ACRYLATE	Ingestion	Rat	LD50 551 mg/kg
ISOOCTYL ACRYLATE	Dermal	Rabbit	LD50 > 2,000 mg/kg
ISOOCIYLACKYLAIE	Ingestion	Rat	LD50 > 5,000 mg/kg
	Dermal	Rabbit	LD50 > 5,000 mg/kg
ISOBORNYL ACRYLATE	Ingestion	Rat	LD50 4,350 mg/kg
1,6-HEXANEDIOL DIACRYLATE	Dermal	Rabbit	LD50 3,636 mg/kg
	Ingestion	Rat	LD50 > 5,000 mg/kg
	Dermal	Rat	LD50 > 2,000 mg/kg
	Inhalation-	Rat	LD50 > 3,055 mg/kg
ORGANIC PIGMENT	Dust/Mist		
	(4 hours)		
	Ingestion	Rat	LD50 > 5,000 mg/kg
9 4 C-TRIMETINI DENZOVI DIDUENNI	Dermal	Professional	LD50 estimated to be
2,4,6-TRIMETHYLBENZOYLDIPHENYL PHOSPHINE		judgement	> 5,000 mg/kg
	Ingestion	Rat	> 5,000 mg/kg
BENZOPHENONE	Dermal	Rabbit	LD50 3,535 mg/kg
DENZOFIENONE	Ingestion	Rat	LD50 1,900 mg/kg

Skin Corrosion/Irritation

Name	Species	Value
TETRAHYDROFURFURYL ACRYLATE	Rabbit	Irritant
ISOBORNYL ACRYLATE	Rabbit	Minimal irritation
1,6-HEXANEDIOL DIACRYLATE	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
TETRAHYDROFURFURYL ACRYLATE	Rabbit	Severe irritant
ISOOCTYL ACRYLATE	Similar health	Mild irritant
	hazards	
ISOBORNYL ACRYLATE	Rabbit	Mild irritant
1,6-HEXANEDIOL DIACRYLATE	Rabbit	Moderate irritant
BENZOPHENONE	Rabbit	Mild irritant



Skin Sensitization

Name	Species	Value
TETRAHYDROFURFURYL ACRYLATE	Human and	Some positive data exist, but the data
	animal	are not sufficient for classification
ISOOCTYL ACRYLATE	Mouse	Sensitizing
ISOBORNYL ACRYLATE	Mouse	Sensitizing
1,6-HEXANEDIOL DIACRYLATE	Guinea pig	Sensitizing

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification

Germ Cell Mutagenicity

Name	Route	Value
ISOOCTYL ACRYLATE		Come accitized at a crist both the date
ISOBORNYL ACRYLATE	In Vitro	Some positive data exist, but the data
1,6-HEXANEDIOL DIACRYLATE		are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
BENZOPHENONE	ngestion	Multiple animal species	Carcinogenic

Reproductive and/or Developmental Effects

Name	Route	Value	Spec	Test	Exposure
			ies	Result	Duration
ISOOCTYL ACRYLATE	Ingestion	Some positive	Rat	NOAEL	during
		developmental data		1,000	organogenesis
		exist, but the data are		mg/kg/day	
		not sufficient for			
		classification			
2,4,6-TRIMETHYLBE	Ingestion	Toxic to male	Rat	NOAEL	90 days
NZOYLDIPHENYLPH		reproduction		100	
OSPHINE				mg/kg/day	
BENZOPHENONE	Ingestion	Some positive	Rab	NOAEL	During



	developmental data	bit	25mg/kg/d	gestation
	exist, but the data are		ay	
	not sufficient for			
	classification			

Specific Target Organ Toxicity - single exposure

Name	Route	Target	Value	Species	Test
		Organ(s)			Result
ISOOCTYL ACRYLATE	Ingestion	central nervous system depression	Some positive	Rat	NOAEL 5,000 mg/kg
ISOBORNYL ACRYLATE	Inhalation	respiratory irritation	data exist, but the data are not	official classifica tion	Not available
TETRAHYDROFURF URYL ACRYLATE	Inhalation	respiratory irritation	sufficient for classification		Not available
1,6-HEXANEDIOL DIACRYLATE	Inhalation	respiratory irritation		Human	Not Available

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target	Value	Species	Test	Exposure
		Organ(s)			Result	Duration
ISOOCTYL ACRYLATE	Ingestion	endocrine system liver kidney and/or		Rat	NOAEL 600 mg/kg/day (Rat, 90	90 days
		bladder	Some positive data exist, but		days)	
2,4,6-TRIMETHYL BENZOYLDIPHE NYLPHOSPHINE	Ingestion	skin blood liver kidney and/or bladder	the data are not sufficient for classification	Rat	NOAEL 1,000 mg/kg/day (Rat, 90 days)	90 days
BENZOPHENONE	Ingestion	heart hematopoieti c system liver		Rat	NOAEL 850 mg/kg/day	14 weeks



		immune				
		system				
BENZOPHENONE	Ingestion	kidney and/or	May cause	Rat	LOAEL 75	14 weeks
		bladder	damage to		mg/kg/day	
			organs though	Mouse	LOAEL 70	80 weeks
1,6-HEXANEDIOL	Dermal	skin	prolonged or		mg/kg/day	
DIACRYLATE			repeated		(Mouse, 80	
			exposure		weeks)	

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification

12. Ecological Information

	Handling is noted because it might influence the environment when leaking and abandoning it.		
	Especially, note that the product doesn't flow directly to ground, the		
	river, and the drain ditch.		
Ecotoxicity	\therefore Please contact the address or phone number listed on the first page of		
	the SDS for additional chemical fate information on this material		
	and/or its components.		
Persistence and	: Not available		
Degradability			
Bioaccumulation	: Not available		
Mobility	: Not available		
Other Toxicity	: Not available		

13. Disposal Considerations

Disposal methods	: Dispose of contents/ container in accordance with the
	local/regional/national/international regulations.
	Dispose of waste product in a permitted industrial waste facility. As a
	disposal alternative, incinerate in a permitted waste incineration
	facility. Proper destruction may require the use of additional fuel
	during incineration processes. Empty drums/barrels/containers used

	for transporting and handling hazardous chemicals (chemical			
	substances/mixtures/preparations classified as Hazardous as per			
	applicable regulations) shall be considered, stored, treated &			
	disposed of as hazardous wastes unless otherwise defined by			
	applicable waste regulations. Consult with the respective regulating			
	authorities to determine the available treatment and disposal			
	facilities.			
	Do not dump this product into sewers, on the ground or into any body			
	of water.			
EPA Hazardous Waste	: Not regulated			
Number (RCRA)				

14. Transport Information

	Check a thing without a leak in a container.		
	Perform prevention of collapse of cargo surely.		
UN Number	: UN3082		
Shipping	: Environmentally hazardous substance, liquid, n.o.s. (ISOOCTYL		
Name	ACRYLATE, ISOBORNYL ACRYLATE)		
Hazardous Class or	: 9		
Division			
Packing Group (PG)	: III		
Remarks	: Single or inner packaging less than 5 L (liquid) or 5 kg net (solids) is		
	excepted from Dangerous Goods regulations.		
	Refer to ICAO/IATAA197, IMDG 2.10.2.7, ADR SP 375.		

15. Regulatory Information

U.S. Federal Regulations

SARA TitleIII	: Immediate Hazard: Yes
Section 311/312	Delayed Hazard: Yes
	Fire: No
	Pressure: No
	Reactive: No

∕∕limcikiĭ

Safety Data Sheets

Ingredient		CAS No.	Regulation	Status	
			Toxic Substances Control Act		
BENZOPHENONE		119-61-9	(TSCA) 4 Test Rule	Applicable	
			Chemicals		
U.S. State Regulations					
California Proposition 65 : WARNING					
This product can expose you to chemicals including					
Benzophenone, Toluene, which are known to the Sta			the State of		
	California to cause cancer/ birth defects or other reproductiv				
harm. For more information go to www.P65Warnings.ca.gov				Varnings.ca.gov	
Chemical Inventories : The components of this product are in compliance with the chemical				with the chemical	
notification requirements of TSCA.					

This material contains a chemical which requires export notification under TSCA Section 12[b]:

16. Other Information

This information is furnished without warranty, express or implied, except that it is accurate to the best knowledge of Mimaki Engineering Corporation.

It relates only to the specific material designated herein, and does not relate to use in combination with any other material or process.

Mimaki Engineering Corporation assumes no legal responsibility for use or reliance upon this information.