

Product Name: LUS-150 Black SDS No. 037-U080296

First issue: 2012/12/06 Revised: 2024/03/03

1. Identification

Product Name : LUS-150 Black Order No. : LUS15-K-BA

Ink Ver. : 1

General Use : Ink jet printing ink

Product Description : UV Inkjet Ink SDS Number : 037- U080296

Manufacture

Company Name : Mimaki Engineering Co., Ltd.

Address : 2182-3 Shigeno-otsu, Tomi-shi, Nagano 389-0512 JAPAN

Telephone No. : +81-268-64-2413

Importer / Distributor Established in USA

Company Name : MIMAKI USA, INC.

Address : 150 Satellite Boulevard, suite A, Suwanee, Georgia 30024, U.S.A.

Telephone No. : +1-678-730-0170

Emergency Telephone No. : +1 866 928 0789 (within United States only)

+1 215 207 0061

2. Hazards Identification

[HCS Classification]

Physical Hazards

Flammable Liquids : Not classified

Health Hazards

Skin Corrosion / Irritation : Category2

Eye Damage / Irritation : Category2

Sensitization - Skin : Category1A

Carcinogenicity : Category 2

Toxic to Reproduction : Category2

Specific Target Organ Toxicity : Category3

(Single Exposure)

Specific Target Organ Toxicity : Category1

(Repeated Exposure)

Environmental Hazards



Product Name: LUS-150 Black SDS No. 037-U080296

> First issue: 2012/12/06 Revised: 2024/03/03

Hazardous to the Aquatic : Category2

Environment - Long Term Hazard

The above list does not include category being non-classifiable or not-applicable.

[HCS Label Elements]

Symbol







Signal Word Danger

Hazard Statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer

H361 Suspected of damaging fertility or the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements

[Prevention]

P201 Obtain SDS (Safety Data Sheet) and printer's Operation Manual before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe gas/mist.

P264 Wash hands and eyes thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

[Response]

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

[Storage]

P403+P233 Store in a well-ventilated place. Keep container tightly closed P405 Store locked up.



Product Name: LUS-150 Black SDS No. 037-U080296 First issue: 2012/12/06

Revised: 2024/03/03

Safety Data Sheets

[Disposal]

P501 Dispose of contents/container in accordance with local/regional/national/international regulation (to be specified).

[Hazards not otherwise classified (HNOC)]

Not classified

[Other hazards]

May be harmful in contact with skin.

Toxic to aquatic life with long lasting effects.

Toxic to aquatic life.

NFPA Rating (scale 0-4)

HMIS Rating (scale 0-4)

Health = 2

Flammability = 1

Instability = 1

Special =



Health = 2

Flammability= 1

Reactivity = 1

Protective Equipment = B



3. Composition / Information on Ingredients

No	Chemical Name	CAS No.	Wt%
1	N-vinylcaprolactam	2235-00-9	15-30
2	Isobornyl acrylate ester	5888-33-5	15-30
3	2-Phenoxyethyl acrylate	48145-04-6	5-10
4	2,4,6-Trimethylbenzoyl diphenyl Phosphine Oxide	75980-60-8	5-10
5	Trimethylolpropane triacrylate	15625-89-5	1-5
6	Tripropylene glycol diacrylate	42978-66-5	0.5-1.5

4. First Aid Measures

[First aid measures for different exposure routes]

General advice : Do not get in eyes, on skin, or on clothing.

If symptoms persist, call a physician.

Eye Contact : IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Skin Contact : IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Inhalation : IF INHALED: Remove to fresh air and keep at rest in a position



Product Name: LUS-150 Black SDS No. 037-U080296

> First issue: 2012/12/06 Revised: 2024/03/03

comfortable for breathing.

Call a POISON CENTER or doctor/physician if you feel unwell.

: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Ingestion

Immediately call a POISON CENTER or doctor/physician.

Protection of First-aiders : Use personal protective equipment.

Most important : May cause redness, itching, and pain. May cause allergic skin

symptoms/effects, acute reaction.

and delayed

Indication of Immediate : May cause sensitization of susceptible persons.

Medical Attention and

Treat symptomatically.

Special Treatment Needed, If necessary

Fire Fighting Measures

Flammable Properties : Not appricable

Suitable Extinguishing : Use extinguishing measures that are appropriate to local

Media circumstances and the surrounding environment.

Unsuitable Extinguishing : Do not use a solid water stream as it may scatter and spread fire.

Media

Special Hazards Arising

from the Chemical

: Thermal decomposition can lead to release of irritating gases and

vapors. In the event of fire and/or explosion do not breathe

fumes. May cause sensitization by inhalation and skin contact. May

cause sensitization by skin contact.

Hazardous Combustion

Products

: Nitrogen oxides (NOx). Carbon oxides.

Explosion Data : Sensitivity to Mechanical Impact; none

Sensitivity to Static Discharge; none

Protective Equipment

: As in any fire, wear self-contained breathing apparatus

and Precautions for

pressure-demand, MSHA/NIOSH (approved or equivalent) and full

Firefighters protective gear.



Product Name: LUS-150 Black SDS No. 037-U080296

> First issue: 2012/12/06 Revised: 2024/03/03

6. Accidental Release Measures

Personal Precautions, : Use personal protective equipment.

Protective Equipment Avoid contact with the skin and the eyes.

and Emergency Evacuate personnel to safe areas.

Procedures Keep people away from and upwind of spill/leak.

Environmental : Prevent entry into waterways, sewers, basements or confined areas.

precautions Do not flush into surface water or sanitary sewer system.

Prevent further leakage or spillage if safe to do so.

Prevent product from entering drains.

Methods and Materials : Methods for Containment

for Containment and Prevent further leakage or spillage if safe to do so.

Cleaning Up Methods for cleaning up

Use personal protective equipment.

Dam up.

Cover liquid spill with sand, earth or other noncombustible absorbent

material.

Take up mechanically, placing in appropriate containers for disposal.

Clean contaminated surface thoroughly. Soak up with inert absorbent material.

Pick up and transfer to properly labeled containers.

7. Handling and Storage

Precautions for Safe : Ensure adequate ventilation.

Handling Wear personal protective equipment.

Use only in area provided with appropriate exhaust ventilation.

Do not breathe vapors or spray mist.

Avoid exposure during pregnancy.

Conditions for Safe : Keep container tightly closed.

onarmons for pare Reep container digitaly closed

Storage, including any Keep containers tightly closed in a cool, well-ventilated place. Keep in

Incompatibilities properly labeled containers.



Product Name: LUS-150 Black SDS No. 037-U080296

> First issue: 2012/12/06 Revised: 2024/03/03

8. Exposure Controls / Personal Protection

[Control parameters]

Exposure Guidelines : This product does not contain any hazardous materials with

occupational exposure limits established by the region specific

regulatory bodies.

[Exposure Controls]

Engineering Measures : Ventilation systems

[Individual Protection Measures, such as Personal Protective Equipment]

Respiratory Protection : If exposure limits are exceeded or irritation is experienced,

NIOSH/MSHA approved respiratory protection should be worn.

Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

Glove : Wear protective gloves/clothing.

Recommendations

Gloves

Eye /Face : Tightly fitting safety goggles. Face-shield.

Protection



Skin Protection : Wear protective gloves/clothing.



General Hygiene : When using do not eat, drink or smoke.

Considerations Take off contaminated clothing and wash before reuse.

Regular cleaning of equipment, work area and clothing is

recommended.

9. Physical and Chemical Properties

Appearance - Physical State : liquid (@20°C)



Product Name: LUS-150 Black SDS No. 037-U080296

> First issue: 2012/12/06 Revised: 2024/03/03

- Color : black

Odor : Acrylates

Odor Threshold : Not available pH : Not available

Specific Gravity : ~ 1.08

Molecular Weight : Not available Flash Point : Not appricable Auto ignition temperature : Not available **Decomposition Temperature** : Not available : 232 °F / 111 °C Boiling Point / Boiling Range Melting Point / Melting Range : Not available Freezing Point : Not available Flammability Limit in Air : Not available Oxidizing Properties : Not available : Not available **Explosive Property Details**

Solubility : Immiscible in water

Partition Coefficient : Not available
Evaporation Rate : Not available

Vapor Pressure : <1 mm/Hg (@ 20 C)

Vapor Density : Not available
Density : Not available

Weight per Gallon (lbs) ~ 9.0 Actual VOC (lb/gal) < 0.18

VOC (lb/gal) : Not available
VOC (g/l) : Not available
Dynamic viscosity : Not available

[VOC Content California]

VOC Content of Material : <22 grams per liter
VOC Content of Coating less Water and Exempt Solvents : <22 grams per liter

10. Stability and Reactivity

Reactivity : Stable under recommended storage conditions.
Chemical Stability : Stable under recommended storage conditions.

Possibility of Hazardous : None under normal processing.

Reactions Hazardous polymerization may occur.



Product Name: LUS-150 Black SDS No. 037-U080296

> First issue: 2012/12/06 Revised: 2024/03/03

Safety Data Sheets

Conditions to Avoid : Extremes of temperature and direct sunlight.

Incompatible Materials : Strong oxidizing agents, strong acids, and strong bases.

Hazardous : Carbon oxides. Nitrogen oxides (NOx).

Decomposition Products

11. Toxicological Information

[Information on likely routes of exposure]

[Product Information]

Acute Toxicity

Inhalation : May be harmful if inhaled. May cause irritation of respiratory tract.

Eyes : Irritating to eyes.

Skin : Irritating to skin. Repeated or prolonged skin contact may cause

allergic reactions with susceptible persons.

May be harmful in contact with skin. May cause inflammation.

Ingestion : Ingestion may cause gastrointestinal irritation, nausea, vomiting and

diarrhea. Ingestion may cause irritation to mucous membranes.

May be harmful if swallowed.

[Component Information]

Chemical Name	Oral LD50	Dermal LD50	LC50 (lethal concentration)
Tripropylene glycol diacrylate	=3,000mg/kg	> 2 g/kg	
	(Rat)	(Rabbit)	

[Information on toxicological effects]

No information available.

[Delayed and immediate effects as well as chronic effects from short and long-term exposure]

Irritation : Irritating to eyes, respiratory system and skin.

Corrosivity : No information available.

Sensitization : May cause sensitization by skin contact.

Mutagenic Effects : No information available.

Reproductive Toxicity : Product is or contains a chemical which is a known or suspected

reproductive hazard.

Carcinogenicity : Trimethylolpropane triacrylate(CAS No. 15625-89-5)

	IARC	Monograph 122 [2019](technical grade)		
		(Group 2B (possibly carcinogenic to humans))		
OSHA Hazard Communicati		Hazard Communication Carcinogens: Present		

STOT - single exposure : No information available.STOT - repeated : No information available.



Product Name: LUS-150 Black SDS No. 037-U080296

> First issue: 2012/12/06 Revised: 2024/03/03

exposure

Chronic toxicity : Experiments have shown reproductive toxicity effects on laboratory

animals. May adversely affect liver and kidney. Repeated contact may

cause allergic reactions in very susceptible persons.

Avoid repeated exposure.

Target Organ Effects : Eyes, Lymphatic System, Respiratory system.

Aspiration hazard : No information available.
[Numerical measures of toxicity - Product Information]

The following values are calculated based on chapter 3.1 of the GHS document.

ATEmix (oral) : 1,212 mg/kg ATEmix (dermal) : 2,667 mg/kg

ATE: Acute toxicity estimate

12. Ecological Information

Handling is noted because it might influence the environment when leaking and abandoning it. Especially, note that the product doesn't flow directly to ground, the river, and the drain ditch.

Ecotoxicity : Toxic to aquatic life with long lasting effects.

Persistence and : No information available.

Degradability

Bioaccumulation :

Chemical Name	Octonol Water Partition Coefficient (log pow)
Tripropylene glycol diacrylate	2.77

Mobility : No information available.

Other adverse effects : No information available.

13. Disposal Considerations

Disposal Methods : Dispose of in accordance with all applicable national environmental

laws and regulations. Dispose of in accordance with federal, state, and

local regulations.

Do not dump this product into sewers, on the ground or into any body

of water.

Contaminated : Do not re-use empty containers.

Packaging



Product Name: LUS-150 Black SDS No. 037-U080296 First issue: 2012/12/06

Revised: 2024/03/03

14. Transport Information

Check a thing without a leak in a container. Perform prevention of collapse of cargo surely.

DOT	Not regulated			
TDG	Not regulated			
MEX	Not regulated			
ICAO	Proper Shipping Name	Environmentally hazardous substance, liquid, n.o.s		
	UN/ID No	UN3082		
	Hazard Class	9		
	Packing Group	III		
	Description	Environmentally hazardous substance, liquid, n.o.s		
IATA	Proper Shipping Name	Environmentally hazardous substance, liquid, n.o.s		
	UN/ID No	UN3082		
	Hazard Class	9		
	Packing Group	III		
	Description	Environmentally hazardous substance, liquid, n.o.s		
IMDG	Proper Shipping Name	Environmentally hazardous substance, liquid, n.o.s		
	UN/ID No	UN3082		
	Hazard Class	9		
	Packing Group	III		
	Description	Environmentally hazardous substance, liquid, n.o.s		
ADR/RID	Proper Shipping Name	Environmentally hazardous substance, liquid, n.o.s		
	UN/ID No	UN3082		
	Hazard Class	9		
	Packing Group	III		
	Description	Environmentally hazardous substance, liquid, n.o.s		

Remarks

: Single or inner packaging less than 5 L (liquid) or 5 kg net (solids) is excepted

from Dangerous Goods regulations.

Refer to ICAO/IATA A197, IMDG 2.10.2.7, ADR SP 375.

15. Regulatory Information

[International Inventories]

TSCA : Yes
DSL/NDSL : Yes
PIC CS : Yes



Product Name: LUS-150 Black SDS No. 037-U080296

> First issue: 2012/12/06 Revised: 2024/03/03

Safety Data Sheets

EINECS/ELINCS : Yes
ENCS : No
IECSC : Yes
KECL : No
AICS : Yes

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

[U.S. Federal Regulations]

TSCA Sections 4, 5 and : This product does not contain any chemicals regulated by TSCA

12(b) Sections 4, 5 or 12(b).

SARA 313 : Section 313 of Title III of the Superfund Amendments and

Reauthorization Act of 1986 (SARA).

This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of

Federal Regulations, Part 372:

Chemical Name	CAS No	SARA 313 - Threshold Values %	Weight-%
2-Phenoxyethyl acrylate	48145-04-6	1.0	5-10

SARA 311/312 Hazard : Acute Health Hazard ; Yes
Categories Chronic Health Hazard ; Yes
Fire Hazard ; No
Sudden Release of Pressure Hazard ; Yes
Reactive Hazard ; Yes

Clean Water Act : This product does not contain any substances regulated as

pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40

CFR 122.42).

^{*}Yes - All component(s) of this product are included or are exempt from listing on the inventory.

^{*}No - Indicates the component(s) of this product are either not listed or have not been determined to be listed on the inventory.



Product Name: LUS-150 Black SDS No. 037-U080296

> First issue: 2012/12/06 Revised: 2024/03/03

CERCLA : This material, as supplied, does not contain any substances

regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act

(CERCLA) (40 CFR 302) or the Superfund Amendments and

Reauthorization Act (SARA) (40 CFR 355).

There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

[U.S. State Regulations]

California Proposition 65

: WARNING:



This product can expose you to chemicals including Carbon black and Trimethylolpropane triacrylate which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

[U.S. State Right-to-Know Regulations]

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
2-Phenoxyethyl acrylate		×	×	×	

[International Regulations]

Canada - NDSL : This product does not contain any NDSL chemicals.

Mexico - Grade : Slight risk, Grade 1
[Mexico - Carcinogen Status and Exposure Limits]

No information available.

[Other Regulations]

No information available.

CPSIA : Formulated to comply.

CONEG : Formulated to comply.

ASTM F-963 : Formulated to comply.

CHPA : Formulated to comply.

ROHS : Formulated to comply.

REACH/SVHC : Formulated to comply.

EN-71 : Formulated to comply.

16. Other Information

This information is furnished without warranty, express or implied, except that it is accurate to the best knowledge of Mimaki Engineering Corporation.



Product Name: LUS-150 Black SDS No. 037-U080296

First issue: 2012/12/06 Revised: 2024/03/03

Safety Data Sheets

It relates only to the specific material designated herein, and does not relate to use in combination with any other material or process.

Mimaki Engineering Corporation assumes no legal responsibility for use or reliance upon this information.