

1. Identification

Product Name	: LUS-150 Light Magenta	
Order No.	: LUS15-LM-BA	
Ink Ver.	:1	
General Use	: Ink jet printing ink	
Product Description	: UV Inkjet Ink	
SDS Number	: 037- U080301	
Manufacture		
Company Name	: Mimaki Engineering Co., Ltd.	
Address	2182-3 Shigeno-otsu, Tomi-shi, Nagano 389-0512 JAPAN	
Telephone No.	: +81-268-64-2413	
Importer / Distributor Established in USA		
Company Name	: MIMAKI USA, INC.	
Address	: 150 Satellite Boulevard, suite A, Suwanee, Georgia 30024, U.S.A.	
Telephone No.	: +1-678-730-0170	
Emergency Telephone No.	: +1 866 928 0789 (within United States only)	
	$+1\ 215\ 207\ 0061$	

2. Hazards Identification		
[HCS Classification]		
Physical Hazards		
Flammable Liquids	: Not classified	
Health Hazards		
Skin Corrosion / Irritation	: Category2	
Eye Damage / Irritation	: Category2	
Sensitization – Skin	: Category1A	
Toxic to Reproduction	: Category2	
Carcinogenicity	Category 2	
Specific Target Organ Toxicity	: Category3	
(Single Exposure)		
Specific Target Organ Toxicity	: Category1	
(Repeated Exposure)		


Environmental Hazards



Hazardous to the Aquatic Environment - Long Term Hazard

: Category2

The above list does not include category being non-classifiable or not-applicable.



Signal Word Danger

Hazard Statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer

H361 Suspected of damaging fertility or the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements

[Prevention]

P201 Obtain SDS (Safety Data Sheet) and printer's Operation Manual before use.

P202 Do not handle until all safety precautions have been read and understood. P260 Do not breathe gas/mist.

P264 Wash hands and eyes thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection. [Response]

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

Storage

P403+P233 Store in a well-ventilated place. Keep container tightly closed P405 Store locked up.



[Disposal]

P501 Dispose of contents/container in accordance with local/regional/national/international regulation (to be specified).

[Hazards not otherwise classified (HNOC)]

Not classified

[Other hazards]

May be harmful in contact with skin.

Toxic to aquatic life with long lasting effects.


Toxic to aquatic life.

NFPA Rating (scale 0-4)

Health = 2 Flammability = 1 Instability = 1 Special =



HMIS Rating (scale 0 - 4)



3. Composition / Information on Ingredients

No	Chemical Name	CAS No.	Wt%
1	Trimethylolpropane formalacrylate	66492-51-1	30-50
2	N-vinylcaprolactam	2235-00-9	10-20
3	Isobornyl acrylate ester	5888-33-5	10-20
4	2-Phenoxyethyl acrylate	48145-04-6	10-20
5	phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide	162881-26-7	1-5
6	Ethylene glycol phenyl ether	122-99-6	1-5
7	Acrylated resin	Proprietary	1-5
8	2,4,6-Trimethylbenzoyl diphenyl Phosphine Oxide	75980-60-8	1-5
9	Trimethylolpropane triacrylate	15625-89-5	1-5
10	Tripropylene glycol diacrylate	42978-66-5	0.5-1.5

4. First Aid Measures

[First aid measures for different exposure routes]

General advice: Do not get in eyes, on skin, or on clothing.If symptoms persist, call a physician.Eye Contact: IF IN EYES: Rinse cautiously with water for several minutes.

	Remove contact lenses, if present and easy to do. Continue rinsing.
	If eye irritation persists: Get medical advice/attention.
Skin Contact	: IF ON SKIN: Wash with plenty of soap and water.
	If skin irritation or rash occurs: Get medical advice/attention.
Inhalation	: Move to fresh air. If symptoms persist, call a physician.
	Artificial respiration and/or oxygen may be necessary.
	Consult a physician. Immediate medical attention is not required.
	Move to fresh air in case of accidental inhalation of vapors.
Ingestion	: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
	Immediately call a POISON CENTER or doctor/ physician.
Protection of First-aiders	: Use personal protective equipment.
Most important	: May cause redness, itching, and pain. May cause allergic skin
symptoms/effects, acute	reaction.
and delayed	
Indication of Immediate	: May cause sensitization of susceptible persons.
Medical Attention and	Treat symptomatically.
Special Treatment	
Needed, If necessary	

5. Fire Fighting Measures

Flammable Properties	: Not appricable
Suitable Extinguishing	: Use extinguishing measures that are appropriate to local
Media	circumstances and the surrounding environment.
Unsuitable Extinguishing	: Do not use a solid water stream as it may scatter and spread fire.
Media	
Special Hazards Arising	: Thermal decomposition can lead to release of irritating gases and
from the Chemical	vapors. In the event of fire and/or explosion do not breathe
	fumes. May cause sensitization by inhalation and skin contact. May
	cause sensitization by skin contact.
Hazardous Combustion	: Nitrogen oxides (NOx). Carbon oxides.
Products	
Explosion Data	: Sensitivity to Mechanical Impact ; none
	Sensitivity to Static Discharge ; none
Protective Equipment	As in any fire, wear self-contained breathing apparatus
and Precautions for	pressure-demand, MSHA/NIOSH (approved or equivalent) and full
and Precautions for	pressure-demand, MSHA/NIOSH (approved or equivalent) and full



Firefighters

protective gear.

6. Accidental Release Measures

Personal Precautions,	: Use personal protective equipment.
Protective Equipment	Avoid contact with the skin and the eyes.
and Emergency	Evacuate personnel to safe areas.
Procedures	Keep people away from and upwind of spill/leak.
Environmental	: Prevent entry into waterways, sewers, basements or confined areas.
precautions	Do not flush into surface water or sanitary sewer system.
	Prevent further leakage or spillage if safe to do so.
	Prevent product from entering drains.
Methods and Materials	: Methods for Containment
for Containment and	Prevent further leakage or spillage if safe to do so.
Cleaning Up	Methods for cleaning up
	Use personal protective equipment.
	Dam up.
	Cover liquid spill with sand, earth or other noncombustible absorbent
	material.
	Take up mechanically, placing in appropriate containers for disposal.
	Clean contaminated surface thoroughly.
	Soak up with inert absorbent material.
	Pick up and transfer to properly labeled containers.

7. Handling and Storage

Precautions for Safe	Ensure adequate ventilation.
Handling	Wear personal protective equipment.
	Use only in area provided with appropriate exhaust ventilation.
	Do not breathe vapors or spray mist.
	Avoid exposure during pregnancy.
Conditions for Safe	: Keep container tightly closed.
Storage, including any	Keep containers tightly closed in a cool, well-ventilated place. Keep in
Incompatibilities	properly labeled containers.



Product Name: LUS-150 Light Magenta SDS No. 037-U080301 First issue: 2015/02/14 Revised: 2024/03/03

8. Exposure Controls / Per	rsonal Protection	
[Control parameters]		
Exposure Guidelines	: This product does not contain any hazardous materials with	
	occupational exposure limits established by the region specific	
	regulatory bodies.	
[Exposure Controls]		
Engineering Measures	: Ventilation systems	
[Individual Protection Meas	sures, such as Personal Protective Equipment]	
Respiratory Protection	: If exposure limits are exceeded or irritation is experienced,	
	NIOSH/MSHA approved respiratory protection should be worn.	
	Positive-pressure supplied air respirators may be required for high	
Vapor Respirator	airborne contaminant concentrations. Respiratory protection must be	
	provided in accordance with current local regulations.	
Glove	: Wear protective gloves/clothing.	
Recommendations		
Gloves		
Eye /Face	: Tightly fitting safety goggles. Face-shield.	
Protection		
Safety Glasses		
Skin Protection	: Wear protective gloves/clothing.	
General Hygiene	: When using do not eat, drink or smoke.	
Considerations	Take off contaminated clothing and wash before reuse.	
	Regular cleaning of equipment, work area and clothing is	
	recommended.	

9. Physical and Chemical Properties

Appearance - Physical State

	- Color	: red
	Odor	Acrylates
	Odor Threshold	: Not available
	pH	: Not available
	Specific Gravity	:~ 1.08
	Molecular Weight	: Not available
	Flash Point	: Not appricable
	Auto ignition temperature	: Not available
	Decomposition Temperature	: Not available
	Boiling Point / Boiling Range	: 232 °F / 111 °C
	Melting Point / Melting Range	: Not available
	Freezing Point	: Not available
	Flammability Limit in Air	: Not available
	Oxidizing Properties	: Not available
	Explosive Property Details	: Not available
	Solubility	: Immiscible in water
	Partition Coefficient	: Not available
	Evaporation Rate	: Not available
	Vapor Pressure	: <1 mm/Hg (@ 20 C)
	Vapor Density	: Not available
	Density	: Not available
	Weight per Gallon (lbs)	:~9.0
	Actual VOC (lb/gal)	:<0.27
	VOC (lb/gal)	: Not available
	VOC (g/l)	: Not available
	Dynamic viscosity	: Not available
[V	OC Content California]	
	VOC Content of Material	: <33 grams per liter
	VOC Content of Coating less Water and	Exempt Solvents : <33 grams per liter

10. Stability and Reactivity

Reactivity	: Stable under recommended storage conditions.
Chemical Stability	: Stable under recommended storage conditions.
Possibility of Hazardous	: None under normal processing.
Reactions	Hazardous polymerization may occur.

Conditions to Avoid	: Extremes of temperature and direct sunlight.
Incompatible Materials	: Strong oxidizing agents, strong acids, and strong bases.
Hazardous	: Carbon oxides. Nitrogen oxides (NOx).
Decomposition Products	

11. Toxicological Information

[Information on likely routes of exposure]		
[Product Information]		
Acute Toxicity		
Inhalation	: May be harmful if inhaled. May cause irritation of respiratory tract.	
Eyes	: Irritating to eyes.	
Skin	: May be harmful in contact with skin. Irritating to skin.	
	Repeated or prolonged skin contact may cause allergic reactions with	
	susceptible persons. May cause inflammation.	
Ingestion	: May be harmful if swallowed. Ingestion may cause gastrointestinal	
	irritation, nausea, vomiting and diarrhea.	
	Ingestion may cause irritation to mucous membranes.	

[Component Information]

Chemical Name	Oral LD50	Dermal LD50	LC50 (lethal concentration)
Ethylene glycol phenyl ether	=1,260 mg/kg	=5 mL/kg	
	(Rat)	(Rabbit)	
Tripropylene glycol diacrylate	=3,000mg/kg	> 2 g/kg	
	(Rat)	(Rabbit)	

[Information on toxicological effects]

No information available.

[Delayed and immediate effects as well as chronic effects from short and long-term exposure]

Irritation	: Irritating to eyes and skin.			
Corrosivity	: No informatio	: No information available.		
Sensitization	: May cause ser	: May cause sensitization by skin contact.		
Mutagenic Effects	: No informatio	n available.		
Reproductive Toxicity	: Product is or contains a chemical which is a known or suspected			
	reproductive hazard.			
Carcinogenicity	[:] Trimethylolpropane triacrylate(CAS No. 15625-89-5)			
	LADO	Monograph 122 [2019](technical grade)		
	IARC	(Group 2B (possibly carcinogenic to humans))		
	OSHA	Hazard Communication Carcinogens: Present		



STOT - single exposure	: No information available.
STOT - repeated	: No information available.
exposure	
Chronic toxicity	: Experiments have shown reproductive toxicity effects on laboratory
	animals. May adversely affect liver and kidney. Repeated contact may
	cause allergic reactions in very susceptible persons.
Target Organ Effects	: Eyes, Lymphatic System, Respiratory system.
Aspiration hazard	: No information available.
[Numerical measures of to:	xicity - Product Information]
The following values a	re calculated based on chapter 3.1 of the GHS document.
ATEmix (oral)	: 1,124 mg/kg
ATEmix (dermal)	÷2,553 mg/kg
ATE: Acute toxicity est	timate

12. Ecological Information

Handling is noted because it might influence the environment when leaking and abandoning it. Especially, note that the product doesn't flow directly to ground, the river, and the drain ditch.

Ecotoxicity		: Toxic to aquatic life with long lasting effects.
-	-	

Persistence and : No information available.

:

Degradability

Bioaccumulation

Chemical Name		Octonol Water Partition Coefficient (log pow)
Ethylene glycol phenyl eth	ner	1.13
Tripropylene glycol diacrylate		2.77
Mobility : N	o informa	tion available.

Other adverse effects

: No information available.

13. Disposal Considerations

Disposal Methods	: Dispose of in accordance with all applicable national environmental
	laws and regulations. Dispose of in accordance with federal, state, and
	local regulations.
	Do not dump this product into sewers, on the ground or into any body
	of water.
Contaminated	: Do not re-use empty containers.



Packaging

14. Transport Information

Check a thing without a leak in a container. Perform prevention of collapse of cargo surely.

DOT	Not regulated		
TDG	Not regulated		
MEX	Not regulated		
ICAO	Proper Shipping Name	Environmentally hazardous substance, liquid, n.o.s	
	UN/ID No	UN3082	
	Hazard Class	9	
	Packing Group	III	
	Description	Environmentally hazardous substance, liquid, n.o.s	
IATA	Proper Shipping Name	Environmentally hazardous substance, liquid, n.o.s	
	UN/ID No	UN3082	
	Hazard Class	9	
	Packing Group	III	
	Description	Environmentally hazardous substance, liquid, n.o.s	
IMDG	Proper Shipping Name	Environmentally hazardous substance, liquid, n.o.s	
	UN/ID No	UN3082	
	Hazard Class	9	
	Packing Group	III	
	Description	Environmentally hazardous substance, liquid, n.o.s	
ADR/RID	Proper Shipping Name	Environmentally hazardous substance, liquid, n.o.s	
	UN/ID No	UN3082	
	Hazard Class	9	
	Packing Group	III	
	Description	Environmentally hazardous substance, liquid, n.o.s	

Remarks : Single or inner packaging less than 5 L (liquid) or 5 kg net (solids) is excepted from Dangerous Goods regulations. Refer to ICAO/IATA A197, IMDG 2.10.2.7, ADR SP 375.

15. Regulatory Information

[International Inventories] TSCA :Yes



DSL/NDSL	: No
PIC CS	: No
EINECS/ELINCS	: Yes
ENCS	: No
IECSC	:Yes
KECL	: No
AICS	:Yes

*Yes - All component(s) of this product are included or are exempt from listing on the inventory.*No - Indicates the component(s) of this product are either not listed or have not been determined to be listed on the inventory.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

[U.S. Federal Regulations]

TSCA Sections 4, 5 and	[:] This product does not contain any chemicals regulated by TSCA
12(b)	Sections 4, 5 or 12(b).
SARA 313	: Section 313 of Title III of the Superfund Amendments and
	Reauthorization Act of 1986 (SARA).
	This product contains a chemical or chemicals which are subject to
	the reporting requirements of the Act and Title 40 of the Code of

Federal Regu	lations.	Part	372:
I CACTAI HOGA	iautono,	I UI U	

Chemical Name	CAS No		- Threshold les %	Weight-%
2-Phenoxyethyl acrylate	48145-04-6 1.		.0	10-20
Ethylene glycol phenyl ether	122-99-6	1	.0	1-5
SARA 311/312 Hazard	Acute Health Hazard		; Yes	
Categories	Chronic Health Hazard		; Yes	
	Fire Hazard		; No	
	Sudden Release of Pressure Hazard		; No	

	Reactive Hazard	; Yes	
Clean Water Act	: This product does not contain any substances regulated as		
	pollutants pursuant to the	e Clean Water Act (40 CFR 122.21 and 40	
	CFR 122.42).		
CERCLA	: This material, as supplie	d, does not contain any substances	
	regulated as hazardous su	bstances under the Comprehensive	
	Environmental Response	Compensation and Liability Act	
	(CERCLA) (40 CFR 302) c	r the Superfund Amendments and	
	Reauthorization Act (SAR	A) (40 CFR 355).	
	There may be specific rep	porting requirements at the local, regional,	
	or state level pertaining to	o releases of this material.	
[U.S. State Regulations]			
California Proposition 65	: WARNING		
	This product can exp	oose vou to chemicals including	



This product can expose you to chemicals including Trimethylolpropane triacrylate which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

[U.S. State Right-to-Know Regulations]

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
2-Phenoxyethyl acrylate		×	×	×	
Ethylene glycol phenyl		×	×		
ether					

[International Regulations]

: This product does not contain any NDSL chemicals.

Mexico - Grade : Slight risk, Grade 1

[Mexico - Carcinogen Status and Exposure Limits]

No information available.

[Other Regulations]

Canada - NDSL

No information available.

CPSIA	: Formulated to comply.
CONEG	: Formulated to comply.
ASTM F-963	: Formulated to comply.
CHPA	: Formulated to comply.
ROHS	: Formulated to comply.
REACH/SVHC	: Formulated to comply.



EN-71

: Formulated to comply.

16. Other Information

This information is furnished without warranty, express or implied, except that it is accurate to the best knowledge of Mimaki Engineering Corporation.

It relates only to the specific material designated herein, and does not relate to use in combination with any other material or process.

Mimaki Engineering Corporation assumes no legal responsibility for use or reliance upon this information.